



ALARMING RATEMETER PM1701M



The PM1701M Alarming Rateometer is specially designed to detect and locate radioactive sources in out-of-the-way places, noisy environments, harsh environments, low visibility places and other adverse conditions.

The device is supplied with a telescopic handle and head phones.

It is recommended to monitor vehicles, territories and facilities as well as to monitor and control the levels of radiation deposited from waste materials and particularly metal scraps.



ALARM

LOCATION

MEASUREMENT

Applications

- Scrap metal facilities
- First responders
- HazMat teams

Features

- Continuous automatic monitoring of radiation background
- Capable to search and locate radiation
- Non-volatile memory for storage and processing of operation history
- Alarming function and a possibility to connect headphones
- PC communication via IR interface
- Easy-to-use
- Waterproof and shockproof case



ALARMING RATEMETER

PMT701M

SPECIFICATIONS

Detector	CsI(Tl) Scintillator
Sensitivity for ¹³⁷Cs, not less	100 s⁻¹/(μSv/h)
Count rate range	1 - 9999 s⁻¹
Energy range	0.06 to 3.0 MeV
Count time: - in the background calibration mode - in the search mode	36 sec 2 sec
Range of coefficient n (number of mean square deviations)	1 to 7
False alarm rate (n = 3), not more	1 min⁻¹
Detection of a source moving at 0.2\pm0.005 m distance and 0.5\pm0.05 m/s velocity (background not more than 0.25 μSv/h)	55 kBq ¹³³Ba
PC communication	Download data and upload instrument set up via IR interface
Environmental: Temperature range Relative humidity	-30 °C to +50 °C (LCD: -15 °C to +50 °C) up to 95 % at 35 °C
Power requirements	one 1.5V AA size battery
Battery lifetime typical	1000 h
Case Protection Class	IP67
Drop test	0.7 m onto concrete floor
Dimensions	54 x 202 x 646 mm
Weight, max.	0.75 kg

Design and specifications of the device can be changed without further notice.

**Meets ANSI N42.33
and ITRAP requirements**

Sales North and South America

Polimaster Inc.
2300 Clarendon Boulevard, Suite 708
Arlington VA, 22201, USA
Phone: +1 703 525-5075
Fax: +1 703 525-5079
E-mail: info@polimaster.us

Sales Europe

Polimaster Instruments UAB
125, Kalvariju St., 3P3/p building,
Vilnius, LT-08221, Republic of Lithuania
Phone: +370 5 210 23 23
Fax: +370 5 210 23 22
E-mail: polimaster@polimaster.lt

Sales Asia, Africa, Australia and Oceania

Polimaster Ltd.
112, Bogdanovich St.,
Minsk, 220040, Republic of Belarus
Phone: +375 17 217 70 80
Fax: +375 17 217 70 81
E-mail: polimaster@polimaster.com